

ANAMMOX TREATMENT OF SWINE WASTEWATER USING IMMOBILIZED TECHNOLOGY

Magrí A.¹, Vanotti M.B.², Szogi A.A.²

¹GIRO Technological Centre, Rambla Pompeu Fabra 1, 08100 Mollet del Vallès, Barcelona, Spain.

²United States Department of Agriculture (USDA), Agricultural Research Service (ARS), Coastal Plains Research Center, 2611 W. Lucas St., Florence, South Carolina 29501, USA. Tel: +1 843 669 5203.

matias.vanotti@ars.usda.gov

1 INTRODUCTION

Appropriate land application of manure nitrogen at agronomic rates must be assured in order to preserve environmental quality of agricultural ecosystems, atmosphere, and water resources. When land is limiting, the combined bioprocess of nitrification-denitrification (NDN) has often been considered for the removal of nitrogen, implying the conversion of ammonium (NH₄⁺) into innocuous dinitrogen gas (N₂) through nitrate (NO₃⁻) as intermediate (Béline *et al.*, 2004; Vanotti *et al.*, 2009). However, significant savings in power requirements for the supplying of oxygen during nitrification are possible considering an alternative nitrogen pathway such as the anaerobic oxidation of ammonium (anammox) (Strous *et al.*, 1997). In addition, organic carbon is needed for heterotrophic denitrification, constraining pretreatments like anaerobic digestion for the production of biogas as renewable energy source (Magrí *et al.*, 2009).

Partial nitrification (PN) coupled with anammox has gained a lot of interest in recent years as a more sustainable alternative than conventional NDN. This PN-anammox process stands for a totally autotrophic strategy for the removal of nitrogen, particularly from wastewaters with high nitrogen and low organic contents (Paredes *et al.*, 2007). Some advantages of PN-anammox process are the reduction on oxygen requirements during nitrification (60% less than complete nitrification), a decrease on the sludge production and dioxide carbon emissions with respect to heterotrophic denitrification, and the possibility of working with higher nitrogen loading rates. Ammonium present in wastewater must be first partially oxidized to nitrite (NO₂⁻) by ammonium oxidizing bacteria (AOB). Subsequently, anammox process results in the combination of ammonium and nitrite under absence of oxygen to form N₂. Optimal molar ratio NO₂⁻/NH₄⁺ of 1.32 was proposed for the influent targeting maximum N-removal efficiencies close to 90% (Strous *et al.*, 1998) (Eq. 1; CH₂O_{0.5}N_{0.15} stands for anammox biomass).



A challenge for the implementation of the anammox process is to ensure biomass retention inside the reactor due to the low growth rates of these bacteria. Use of immobilization technologies may result in better biomass retention, minimizing risks of washout, and positively affect the treatment process capacity. The objective of this work was to develop applications of anammox bacteria for the treatment of swine wastewaters using microbial immobilization techniques such as surficial attachment and gel carrier entrapment.

2 MATERIALS AND METHODS

The research was conducted at the ARS Coastal Plains Research Center in Florence, South Carolina. Anammox biomass isolated in previous research (Vanotti *et al.*, 2006; Szogi *et al.*, 2007) was used in the immobilized reactors.

2.1 Molecular techniques

Enriched biomass was characterized using culture-independent techniques. Chromosomal DNA was extracted and 16S ribosomal DNA gene was amplified using the polymerase chain reaction (PCR) according to Fujii *et al.* (2002). Cloning techniques were applied, and finally cloned PCR products were sequenced. Such sequences were submitted to the blast search engine of the GenBank database (Altschul *et al.*, 1997) to obtain putative phylogenetic assignment.

2.2 Experimental set-ups

Two different strategies for immobilizing the anammox bacteria were used (Figure 1):

1) *Attached biomass*: A 10-L pilot reactor was operated in continuous flow configured so that influent wastewater was injected at the bottom-end and the treated effluent was discharged near the top after passing through a matrix of immobilized anammox. Such cylindrical bioreactor was made of glass being jacketed on the outside to control process temperature (30°C). A biomass carrier was placed inside the reactor made of a polyester non-woven material coated with pyridinium type polymer (Japan Vilene Co., Japan), designed to enhance retention of microorganisms (Furukawa *et al.*, 2003). The reactor was continuously fed with synthetic substrate under a flow rate of 60 L d⁻¹ during a 350-day time period.

2) *Entrapped biomass*: A 1-L bench reactor was operated in continuous flow containing anammox biomass entrapped in polyvinyl alcohol (PVA) pellets. Encapsulation procedure was performed according to the methodology described by Vanotti and Hunt (2000) using PVA-HC (100% saponification, 2000 polymerization) (Kuraray Co., Japan). Partially nitrified swine wastewater was continuously supplied as feed and process temperature was controlled at 30°C.




FIGURE 1 View of bioreactors with immobilized anammox bacteria used in this research. *Left*: upflow reactor with attached biomass. *Right*: scheme of the reactor with encapsulated biomass.

2.3 Analytical methods

Nitrogen concentrations of filtrated samples were measured using an auto-analyzer (Technicon Instruments Corp., USA) and according to APHA *et al.* (1998). NH₄-N was determined by the automated phenate method (4500-NH₃ G), NO₂-N was determined by the colorimetric method (4500-NO₂⁻ B), and NO₃-N was determined by the automated cadmium reduction method (4500-NO₃⁻ F). Total nitrogen (TN) was calculated as the sum of NH₄-N, NO₂-N and NO₃-N. Total alkalinity was determined by acid titration to an endpoint of pH 4.5 and expressed as mg CaCO₃ L⁻¹.

3 RESULTS AND DISCUSSION

3.1 Microbiology

Due to the relatively low DNA sequence homology and phylogenetic relationships, the dominant anammox bacteria was proposed as a novel species of the *Candidatus* “Brocadia” genera, being this novel anammox species named *Candidatus* “Brocadia caroliniensis” (Vanotti *et al.*, 2010) (Figure 2). A strain of *B. caroliniensis* was deposited under the provisions of the Budapest Treaty in Agricultural Research Culture Collection (NRRL) in Peoria, Ill., and has been assigned accession deposit number NRRL B-50286.




FIGURE 2 **Bootstrapped (n = 1000) neighbour joining phylogenetic tree of NRRL B-50286 identified as *Candidatus “Brocadia caroliniensis”* in relation to major genera of anammox bacteria found in the GenBank database (Vanotti *et al.*, 2010).**

3.2 Anammox attached biomass

Data in Table 1 summarizes stabilized performance obtained in the continuous flow pilot reactor. Average nitrogenous composition of substrate was of $283.4 \pm 22.4 \text{ mg N L}^{-1}$ ($131.4 \pm 13.0 \text{ mg NH}_4\text{-N L}^{-1}$, $152.0 \pm 13.0 \text{ mg NO}_2\text{-N L}^{-1}$, and $0.1 \pm 0.6 \text{ mg NO}_3\text{-N L}^{-1}$). Under hydraulic retention times (HRT) of 3.9 h, the average total nitrogen loading rate (NLR) was $1.74 \text{ kg N m}^{-3} \text{ d}^{-1}$ and the total nitrogen removal rate (NRR) was $1.48 \text{ kg N m}^{-3} \text{ d}^{-1}$. At these high mass N loading, the average removal efficiency obtained was 85%. Similarly, the ammonium and nitrite were removed at efficiencies of 89 and 98%, respectively. Removal of NH_4^+ and NO_2^- was at stoichiometric ratios summarized as $\text{NH}_4^+ + 1.30 \text{ NO}_2^- \rightarrow 1.06 \text{ N}_2 + 0.18 \text{ NO}_3^-$ (Vanotti *et al.*, 2010).

TABLE 1 **Removal of nitrogen in upflow continuous pilot reactor**

	Mass Nitrogen			Removal efficiency
	Influent	Effluent	Removal	
	-----mg N L ⁻¹ d ⁻¹ -----			-----%-----
TN	1,735 ±137	260 ±122	1,477 ±168	85 ± 7
NH ₄ -N	804 ±80	92 ±71	709 ±88	89 ± 9
NO ₂ -N	930 ±80	22 ±47	915 ±90	98 ± 5
NH ₄ -N + NO ₂ -N	1,735 ±138	114 ±101	1,621 ±155	94 ± 6

3.3 Anammox entrapped biomass

Encapsulation of anammox bacteria in polymer gel carrier has been applied successfully for treatment of digester liquors using polyethylene glycol (PEG) as entrapment polymer (Isaka *et al.*, 2007; Furukawa *et al.* 2009). Under such reactor configuration, influent contents on total suspended solids up to 2000-3000 mg L⁻¹ have been demonstrated as non-limitant for the activity of anammox bacteria. In this work, PVA was used for the immobilization of anammox bacteria (packing ratio of 25%). Partially nitrified wastewater was fed as influent being the NO₂-N/NH₄-N ratio adjusted to the desired value of 1.32 by adding raw wastewater ($1,400 \pm 36 \text{ mg NH}_4\text{-N L}^{-1}$; $7,740 \pm 128 \text{ mg CaCO}_3 \text{ L}^{-1}$).

4 CONCLUSIONS

New bacteria strain *Candidatus “Brocadia caroliniensis”* was identified in anammox enrichment started-up from animal waste sludge. The use of immobilization techniques enhanced anammox biomass retention inside the reactors and resulted in high nitrogen removal rates. These findings overall may lead to the development of more economical treatment systems for swine wastewater effluents containing high ammonium and low biodegradable organic carbon concentrations.

ACKNOWLEDGEMENTS

This research was part of USDA-ARS National Program 214: Utilization of Manure and Other Agricultural and Industrial Byproducts, ARS Project 6657-13630-003-00D “Innovative Bioresource Management Technologies for Enhanced Environmental Quality and Value Optimization”. We thank DURSI Agency (Generalitat de Catalunya) for funding Dr. Magrí’s scientific visit to USDA-ARS Coastal Plains Research Center through award 2009 BE2 00032.

REFERENCES

- Altschul S F, Gish W, Miller W, Myers E W, Lipman D J 1990. Basic local alignment search tool. *Journal of Molecular Biology* 215, 403-410.
- APHA, AWWA, WEF (ed.) 1998. Standard methods for the examination of water and wastewater. 20th ed. Washington DC, USA.
- Béline F, Daumer M L, Guiziou F 2004. Biological aerobic treatment of pig slurry in France: nutrients removal efficiency and separation performances. *Transactions of the ASAE* 47, 857-864.
- Fujii T, Sugino H, Rouse J D, Furukawa K 2002. Characterization of the microbial community in an anaerobic ammonium-oxidizing biofilm cultured on a nonwoven biomass carrier. *Journal of Bioscience and Bioengineering* 94, 412-418.
- Furukawa K, Inatomi Y, Qiao S, Quan L, Yamamoto T, Isaka K, Sumino T 2009. Innovative treatment system for digester liquor using anammox process. *Bioresource Technology* 100, 5437-5443.
- Furukawa K, Rouse J D, Yoshida N, Hatanaka H 2003. Mass cultivation of anaerobic ammonium-oxidizing sludge using a novel nonwoven biomass carrier. *Journal of Chemical Engineering of Japan* 36, 1163-1169.
- Isaka K, Date Y, Sumino T, Tsuneda S 2007. Ammonium removal performance of anaerobic ammonium-oxidizing bacteria immobilized in polyethylene glycol gel carrier. *Applied Microbiology and Biotechnology* 76, 1457-1465.
- Magrí A, Guivernau M, Baquerizo G, Viñas M, Prenafeta-Boldú F X, Flotats X 2009. Batch treatment of liquid fraction of pig slurry by intermittent aeration: process simulation and microbial community analysis. *Journal of Chemical Technology and Biotechnology* 84, 1202-1210.
- Paredes D, Kusch P, Mbvette T S A, Müller R A, Köser H 2007. New aspects of microbial nitrogen transformations in the context of wastewater treatment - a review. *Engineering in Life Sciences* 7, 13-25.
- Strous M, Heijnen J J, Kuenen J G, Jetten M S M 1998. The sequencing batch reactor as a powerful tool for the study of slowly growing anaerobic ammonium-oxidizing microorganisms. *Applied Microbiology and Biotechnology* 50, 589-596.
- Strous M, van Gerven E, Zheng P, Kuenen J G, Jetten M S M 1997. Ammonium removal from concentrated waste streams with the anaerobic ammonium oxidation (ANAMMOX) process in different reactor configurations. *Water Research* 31, 1955-1962.
- Szogi A A, Vanotti M B, Garcia-Gonzalez M C, Kunz A 2007. Development of Anammox process for animal waste treatment: Experiences in the USA. In: *International symposium on air quality and waste management for agriculture*. Broomfield, Colorado, USA. ASABE PN 701P0907, available in CD-Rom.
- Vanotti M B, Hunt P G 2000. Nitrification treatment of swine wastewater with acclimated activated sludge immobilized in polymer pellets. *Transactions of the ASAE* 43, 405-413.
- Vanotti M B, Szogi A A, Kunz A, Garcia-Gonzalez M C 2006. Development of anaerobic ammonium oxidation (Anammox) technology using immobilized biomass from swine manure. In: *Technology for recycling of manure and organic residues in a whole-farm perspective*. Petersen S O (ed.). 12th RAMIRAN International Conference. Aarhus, Denmark, pp. 143-146.
- Vanotti M B, Szogi A A, Millner P D, Loughrin J H 2009. Development of a second-generation environmentally superior technology for treatment of swine manure in the USA. *Bioresource Technology* 100, 5406-5416.
- Vanotti M B, Szogi A A, Rothrock M J 2010. Novel anammox (anaerobic ammonium oxidation) bacterium. US Patent Application SN 61/298,952, filed 1/28/2010. US Patent and Trademark Office, Washington, DC.